

Multiwall



Fixed Output



>50.000 hrs
at L80B10



L100/CLO
optional



PowerFactor
>0.9



LED



Internal



Sensor
optional

About the Multiwall


The Britelight Multiwall is suitable for ceilings and walls. Available in three sizes. With a simple switch, you can alternate between the light color and/or the light intensity.

For extra convenience, opt for the integrated motion detector. It is also possible to equip the lamp with a decentralized emergency unit.



CE IP54

Light beams



Wide

Dimensions


Diameter: 27 cm / 40 cm / 50 cm




Versions

The options under the bullets can be filled in at the places in the table. Additions count as extras behind the code.


Color fixture	●	Optics	●	Driver	●	Additions	●
Opal	W	Optics 90 degrees	OWI	Fixed - 50.000 hrs	F7	Emergency unit	NOOD



Code		Diameter cm	Lifetime hrs	Temp. K	Color CRI	Output lm	Power W	Efficacy lm/W
BLMUWA 0270 2500		27	50.000	3.000 / 4.000	>80	1.100	10	104-110
	2.100					18		
	2.500					24		



Code		Diameter cm	Lifetime hrs	Temp. K	Color CRI	Output lm	Power W	Efficacy lm/W
BLMUWA 0400 2500		40	50.000	3.000 / 4.000	>80	1.100	10	104-110
	2.100					18		
	2.500					24		



Code		Diameter cm	Lifetime hrs	Temp. K	Color CRI	Output lm	Power W	Efficacy lm/W
BLMUWA 0500 2500		50	50.000	3.000 / 4.000	>80	1.100	10	104-110
	2.100					18		
	2.500					24		